



High-flow laundry dosing system

The BrightLogic high-flow laundry dosing systems for industrial laundries can dose from 1 to 10 chemicals with a flow rate of up to 30oz* per minute.

The high-flow pumps can be mixed with on-premise laundry dosing pumps to suit various dosing needs. They are compatible with both intelligent and non-intelligent machines up to 220 lbs** and can be used in relay mode or with a formula select programmer.

Branding options are available to add the name, the logo or the contact details of any company to the dosing system.

**Flow rate tested with water using BrightChem under laboratory conditions*

*** Depending on oz/lbs.*

Features

Hardware features

- Advanced PCB hardware
- Brushless motors (click for image)
- 16 x 4 character illuminated screen (click for image)
- Bluetooth comms
- Configure any combination 1 - 10 pumps (click for image)
- Easy add-on pump configuration (click for image)
- Full speed control on all pumps
- Full range of accessories to suit your installation
- Formula select module available for easy access to programme selection (click for image)
- Independently CE and UL approved

Software features

- Programme formula select with wash cycle names (click for image)
- Chemical usage report including selectable date & time range feature
- Prime and stop pumps from the formula select
- Bespoke access codes and screen text
- Twenty programmes as standard
- Service technician's test screen to view signal inputs
- Auto formula select setting
- Multilingual programming
- Free programming software (click for image)
- Relay mode, standard mode and levels mode

- Branding available (click for image)

Technical Specifications

V
o
l
t
a
g
e
r
e
n
c
y

H
2
:
.
8
A
(
1
V
)
-
.
2
8
A
(
2
4
V
)
H
4
:
1
.
6
A
(
1
V
)
-
.
5
5
A
(
2
4
V
)
H
6
:
2
.
4
A
C
ù
W
f
e
n
B
5
A
(
2
4
V
)
H
8
:
3
.
2
A
(
1
V
)
-
1
.
8
A
(
2
4
V
)
H
1
:
4
A
(
1
V
)
-
1
.
3
6
A
(
2
4
V
)

H
2
:
7
2
W
H
4
:
1
4
4
W
H
B
o
w
e
6
W
H
8
:
2
8
8
W
H
1
:
3
6
W
S
L
g
a
V
S
G
P
D
C
F
I
u
s
h
V
a
l
v
e
2
4
V
D
C
,
1
.
2
5
A
(
1
W
D
n
b
p
b
t
s
z
e
r
/
L
a
m
p
2
4
V
D
C
5
M
a
.
(
1
W
)
m
a
x

1
6
x
4
i
l
l
u
m
i
n
a
t
e
d
L
C
D
d
i
s
p
l
a
y
.
p
r
o
g
r
a
m
m
t
n
g
v
C
b
e
u
t
e
r
y
a
l
k
e
y
p
a
d
k
e
y
s
,
S
e
c
u
r
i
t
y
a
c
c
e
s
s
c
o
d
e
B
r
u
s
h
l
i
g
h
t
w
e
l
l
i
n
c
o
r
p
o
r
a
t
e
d
L
t
d
C
,
6
m
A

G
l
a
s
s
-
F
i
l
l
E
d
e
b
b
y
p
r
e
p
y
l
e
n
e
l
p
4
5
A
y
a
n
t
s
r
a
a
p
|
e
n
c
o
r
p
o
r
a
t
i
o
n
s
l
i
m
i
t
E
M
C
8
9
/
3
3
6
/
E
E
C
E
N
6
1
-
6
-
4
:
A
p
p
l
i
c
a
t
i
o
n
s
/
E
E
C
E
N
6
3
3
5
-
1
:
2
2
+
A
2
:
2
6

H
2
-
1
1
1
/
4
"
x
1
4
3
/
4
"
x
5
1
/
2
"
H
4
-
1
1
1
/
4
"
x
2
8
3
/
4
"
x
5
1
/
2
"
H
6
-
1
1
1
/
4
"
x
5
7
1
/
4
"
x
5
1
/
2
"
H
1
-
1
1
1
/
4
"
x
7
1
1
/
2
"
x
5
1
/
2
"

H
2
-
7
.
5
I
b
s
H
4
-
1
2
I
b
s
H
W
e
i
l
i
g
h
t
b
s
H
8
-
2
2
I
b
s
H
1
-
2
7
I
b
s
M
a
x
i
m
i
z
e
d
l
a
u
n
d
r
y

Installation schematics



Installation kit

Standard installation kits for high-flow laundry include:

1. tubing
2. herby clips
3. a sinker support and filter



Computer software

